

**ERGONOMIC SERIES: Stereo Audio 2 x RCA <==> Stereo Audio 2 x RCA**



<b>Connector left &lt;==&gt; right:</b>	<b>Stereo Audio 2 x RCA &lt;==&gt; Stereo Audio 2 x RCA</b>
Connection-No.:	<b>1</b>
Description:	Stereo Audio connection cable, analog
<b>Connection of (output &lt;==&gt; input):</b> (More connecting options see <a href="#">cable guide connection table</a> )	Amplifier <==> CD Recorder / Mini Disc Amplifier <==> Tape Deck AV Receiver <==> CD Recorder AV Receiver <==> Tape Deck Blu-ray <==> Amplifier Blu-ray <==> AV Receiver Blu-ray <==> Blu-ray Recorder Blu-ray <==> CD Recorder / Mini Disc Blu-ray <==> DVD Recorder Blu-ray <==> Beamer Blu-ray <==> TV / LCD / Plasma Blu-ray <==> Video Recorder CD <==> Amplifier CD <==> AV Receiver CD <==> CD Recorder / Mini Disc CD <==> (Media)-PC / Laptop CD <==> Tape Deck DVD <==> Amplifier SAT Receiver, Set Top Box <==> Amplifier Tape Deck <==> CD Recorder Tape Deck <==> (Media)-PC / Laptop Tape Deck <==> Tape Deck Video Recorder <==> Amplifier
Available lengths:	0.75 m · 1.5 m · 3 m · 5 m
<b>TECHNICAL DATA:</b>	
Material,jacket Ø:	S-PVC 2 x 5,0 mm
No. of inner conductors:	2 x AWG26
CU quality grade:	OxygenFreeCopper Class 4 (99.99 %)
Conductor insulation:	Skin PE
Shielding:	1 x copper braiding, tined + AL/PT-foil
Shielding factor:	100 %
Temperature range:	-25 °C...+75 °C
Capac. cond./shield. @ 1 m:	75 pF
Surge impedance:	50 Ohm ±2 %

Signal transmission or shielding coefficient:	-
Band width:	-
Connector material:	Polyamide
Contacts:	Brass 5 µm Au hard alloy
Guarantee period:	5 years
<b>ORDER-NO.:</b>	<b>HIE-C2C2-LENGTH (e.g. HIE-C2C2-0075)</b>