

AMBIENCE SERIES: SPDIF 75 Ohm / 1 x RCA <==> SPDIF 75 Ohm / 1 x RCA



Connector left <==> right:	SPDIF 75 Ohm / 1 x RCA <==> SPDIF 75 Ohm / 1 x RCA
Connection-No.:	3
Description:	SPDIF 75 Ohm connection cable, digital
Connection of (output <==> input): (More connecting options see cable guide connection table)	AV Receiver <==> Beamer AV Receiver <==> Subwoofer (active) AV Receiver <==> TV / LCD / Plasma CD <==> Amplifier CD <==> AV Receiver CD <==> CD Recorder / Mini Disc CD <==> (Media-) PC / Laptop DVD <==> Amplifier DVD <==> AV Receiver SAT Receiver, Set Top Box <==> Amplifier SAT Receiver, Set Top Box <==> AV Receiver
Available lengths:	1.5 m · 3 m · 5 m · 10 m
TECHNICAL DATA:	
Material, jacket Ø:	S-PVC 2 x 8,0 mm
No. of inner conductors:	2 x AWG24
CU quality grade:	OxygenFreeCopper Class 6 (99.9999 %)
Conductor insulation:	Skin PE
Shielding:	copper braiding, tined + 2 x AL/PT-foil
Shielding factor:	100 %
Temperature range:	-25 °C...+75 °C
Capac. cond./shield. @ 1 m:	67 pF
Surge impedance:	75 Ohm ±2 %
Signal transmission or shielding coefficient:	-
Band width:	-
Connector material:	ZnAl4Cu1 diecast velvet-chrome
Contacts:	Brass 10µm Au hard alloy
Guarantee period:	10 years
ORDER-NO.:	HIA-C1C1-LENGTH (e.g. HIA-C1C1-0150)