

ERGONOMIC SERIES: Component YUV 3 x RCA <==> Component YUV 3 x RCA



| | |
|---|--|
| Connector left <==> right: | Component YUV 3 x RCA <==> Component YUV 3 x RCA |
| Connection-No.: | 5 |
| Description: | Component YUV connection cable, analog also usable as Composite AV |
| Connection of (output <==> input): (More connecting options see cable guide connection table) | AV Receiver <==> Blu-ray Recorder AV Receiver <==> DVD Recorder AV Receiver <==> (Media-) PC Laptop AV Receiver <==> Projector Beamer AV Receiver <==> TV / LCD / Plasma AV Receiver <==> Video Recorder Blu-ray <==> AV Receiver Blu-ray <==> Blu-ray Recorder Blu-ray <==> DVD Recorder Blu-ray <==> (Media-) PC Laptop Blu-ray <==> Projector / Beamer Blu-ray <==> TV / LCD / Plasma DVD <==> AV Receiver DVD <==> Blu-ray Recorder DVD <==> DVD Recorder DVD <==> (Media-) PC Laptop DVD <==> Projector / Beamer DVD <==> TV / LCD / Plasma (Media-) PC Laptop <==> Blu-ray Recorder (Media-) PC Laptop <==> DVD Recorder (Media-) PC Laptop <==> (Media-) PC Laptop (Media-) PC Laptop <==> Beamer (Media-) PC Laptop <==> TV / LCD / Plasma SAT Receiver, Set Top Box <==> AV Receiver SAT Receiver, Set Top Box <==> Blu-ray Recorder SAT Receiver, Set Top Box <==> DVD Recorder SAT Receiver, Set Top Box <==> (Media-) PC Laptop SAT Receiver, Set Top Box <==> Beamer SAT Receiver, Set Top Box <==> TV / LCD / Plasma Video Recorder <==> AV Receiver Video Recorder <==> Blu-ray Recorder Video Recorder <==> DVD Recorder Video Recorder <==> (Media-) PC Laptop Video Recorder <==> TV / LCD / Plasma Video Recorder <==> Video Recorder |
| Available lengths: | 0.75 m · 1.5 m · 3 m · 5 m |

| | |
|---|---|
| TECHNICAL DATA: | |
| Material, jacket Ø: | S-PVC 3 x 5.0 mm |
| No. of inner conductors: | 3 x AWG26 |
| CU quality grade: | OxygenFreeCopper Class 4 (99.99 %) |
| Conductor insulation: | PE |
| Shielding: | 1 x copper braiding, tined + AL/PT-foil |
| Shielding factor: | 100 % |
| Temperature range: | -20 °C...+75 °C |
| | |
| Capac. cond./shield. @ 1 m: | 75 pF |
| Surge impedance: | 75 Ohm ±2 % |
| Signal transmission or shielding coefficient: | - |
| Band width: | - |
| Connector material: | Polyamide |
| Contacts: | Brass 5 µm Au hard alloy |
| Guarantee period: | 5 years |
| | |
| ORDER-NO.: | HIE-CYCY-LENGTH (e.g. HIE-CYCY-0075) |