

ERGONOMIC SERIES: Optical Toslink <==> Optical Toslink


Connector left <==> right:	Optical Toslink <==> Optical Toslink
Connection-No.:	8
Description:	Optical Toslink connection cable, digital
Connection of (output <==> input): (More connecting options see cable guide connection table)	AV Receiver <==> CD Recorder / Mini Disc AV Receiver <==> DVD Recorder CD <==> Amplifier CD <==> AV Receiver CD <==> CD Recorder / Mini Disc CD <==> (Media-) PC Laptop DVD <==> Amplifier Game Controller <==> Amplifier (Media-) PC Laptop <==> (Media-) PC Laptop SAT Receiver, Set Top Box <==> Amplifier
Available lengths:	0.75 m · 1.5 m · 3 m · 5 m
TECHNICAL DATA:	
Material,jacket Ø:	S-PVC 5.0 mm
No. of inner conductors:	PMMA Fiber simplex 980/1000 µm
CU quality grade:	
Conductor insulation:	PE
Shielding:	
Shielding factor:	
Temperature range:	-40 °C...+85 °C
Capac. cond./shield. @ 1 m:	
Surge impedance:	
Signal transmission or shielding coefficient:	0,16 dB @ 650 nm wave length
Band width:	-
Connector material:	Polyamide
Contacts:	Brass 5 µm Au hard alloy
Guarantee period:	5 years
ORDER-NO.:	HIE-TLTL-LENGTH (e.g. HIE-TLTL-0075)