

AMBIENCE SERIES: Sat F-Plug <==> Sat F-Plug



Connector left <==> right:	Sat F-Plug <==> Sat F-Plug
Connection-No.:	9
Description:	SAT-/F-connection cable, analog
Connection of (output <==> input): (More connecting options see cable guide connection table)	SAT TV <==> SAT Receiver SAT TV <==> TV / LCD / Plasma
Available lengths:	0.75 m · 1.5 m · 3 m · 5 m · 10 m
TECHNICAL DATA:	
Material, jacket Ø:	S-PVC 8.0 mm
No. of inner conductors:	1 x AWG18
CU quality grade:	OxygenFreeCopper Class 6 (99.9999 %)
Conductor insulation:	Skin PE
Shielding:	2 x copper braiding, tined + 2 x AL/PT-foil
Shielding factor:	100 %
Temperature range:	-25 °C...+75 °C
Capac. cond./shield. @ 1 m:	65 pF
Surge impedance:	75 Ohm ±2 %
Signal transmission or shielding coefficient:	>120 dB
Band width:	-
Connector material:	ZnAl4Cu1 diecast velvet-chrome
Contacts:	Brass 10 µm Au hard alloy
Guarantee period:	10 years
ORDER-NO.:	HIA-FMFM-LENGTH (e.g. HIA-FMFM-0075)