

Floor Pockets FP1 and FP-2



Constructed of 11 gauge steel, the FP-1 and FP-2 permit flush installation for safe, reliable connections. Each unit incorporates a black carpet trim ring with a beveled edge.

Cable-clearance slots in the doors allow them to close over cables when in use.

Interchangeable end panels are supplied with the FP-1 and FP-2. One is solid metal which allows the user to punch or drill it to their own individual specifications. The other is pre-punched to accept four Whirlwind XLR or TRS jacks. The FP-1 has one interchangeable panel on one end, the FP-2 provides panels on both ends.

The bottom plates are also removable to facilitate additional hole punching and connector mounting. Any or all of these may be ordered custom punched and/or loaded by Whirlwind.

The optional back boxes (FP-1BB, FP-1BB6, FP-2BB and FP-2BB6) have three sets of knockouts on each side.

The FP-1 and FP-2 are UL-listed and CSA approved.

Nominal Outside Dimensions:

FP-1:

Box: 6 1/8" x 6 1/8" x 2.58"

Lid: 8" x 8"

FP-2:

Box: 12" x 6 1/8" x 2.58"

Lid: 14" x 8"

FP-1BB: 6" x 6" x 4"

FP-1BB6: 6" x 6" x 6"

FP-2BB: 6" x 12" x 4"

FP-2BB6: 6" x 12" x 6"

(Click [here](#) to view a detailed spec sheet, 361KB in PDF format.)